



Features

- Aluminum 6063, good heat radiation with long lifespan;
- Support 0~10V, PWM and Resistor dimming solution;
- High lighting efficiency, save energy;
- Long lifespan, ≥ 50000 hours;
- Light source adopts LM-80 certified LED;
- Adopt UL Class P certified power supply;


Parameter

Size	2449mm(8.03ft)X90mm(0.3ft)X86mm(0.28ft)
Beam angle	98°(PDM)
Working voltage	100~277VAC /50~60Hz
PF	≥ 0.9
Input power	90W (11.3W/ft)
CCT	3000K/4000K/6000K (3500K 、 5000K)
CRI	80+/90+
Lumen	9425~10000lm(1177~1250lm/ft)
Energy efficiency	A+
Dimming range	1~100%
Operating temperature	-20°C~+45°C
Storage temperature	-40°C~+60°C
Humidity	40~75% RH
IP grade	IP40
Installation way	Recessed
Package size	2570mm(8.43ft)X145mm(0.48ft)X135mm(0.44ft)
Gross Weight	8.64Kg


Test report




Size



Standard color



PDM



UGR < 19

Remark:

- Output data is from test result of 4ft PDM linear light fixture;
- Tolerance $\pm 10\%$;

Optional accessories

Installation accessories





- Recessed installation

L5570-BI

L5570-BI: Recessed bracket

Connection solution




Ac in line


- Connection

Ac in line: AC input cable

Disassembly tool



L-DA-D



L-DA-A

- Tool

L-DA-D: disassembly tool

L-DA-A: Rubber sucker