


Features

- Aluminum 6063, good heat radiation with long lifespan;
- Support 0~10V, PWM and Resistor dimming solution;
- High lighting efficiency, save energy;
- Long lifespan, ≥ 50000 hours;
- Light source adopts LM-80 certified LED;
- Adopt UL Class P certified power supply;



Parameter

Size	1850mm(6.07ft)X86mm(0.28ft)X36mm(0.12ft)
Beam angle	99°(PDM)
Working voltage	100~277VAC /50~60Hz
PF	≥ 0.9
Input power	51W (8.5W/ft)
CCT	3000K/4000K/6000K (3500K 、 5000K)
CRI	80+/90+
Lumen	4640~4925lm(772~821lm/ft)
Energy efficiency	A+
Dimming range	1~100%
Operating temperature	-20°C~+45°C
Storage temperature	-40°C~+60°C
Humidity	40~75% RH
IP grade	IP40
Installation way	Recessed
Package size	1890mm(6.20ft)X115mm(0.38ft)X92mm(0.3ft)
Gross Weight	3.78Kg



Size



Standard color




PDM



UGR<19


Installation accessories



- N Shape clip




R8636-BI



- Butterfly clip



R-BI



- Rubber sucker



L-DA-A

Remark:

- Output data is from test result of 4ft PDM linear light fixture;
- Tolerance $\pm 10\%$;

Test report

