


Features

- Aluminum 6063, good heat radiation with long lifespan;
- Support 0~10V, PWM and Resistor dimming solution;
- High lighting efficiency, save energy;
- Long lifespan, ≥ 50000 hours;
- Light source adopts LM-80 certified LED;
- Adopt UL Class P certified power supply;

Parameter

Size	1230mm(4.04ft)X73mm(0.24ft)X80mm(0.26ft)
Beam angle	96°(PDM)
Working voltage	100~277VAC /50~60Hz
PF	≥ 0.9
Input power	34W (8.5W/ft)
CCT	3000K/4000K/6000K (3500K 、 5000K)
CRI	80+/90+
Lumen	3345~3465lm(836~866lm/ft)
Energy efficiency	A+
Dimming range	1~100%
Operating temperature	-20°C~+45°C
Storage temperature	-40°C~+60°C
Humidity	40~75% RH
IP grade	IP40
Installation way	Recessed
Package size	1280mm(4.20ft)X130mm(0.43ft)X126mm(0.41ft)
Gross Weight	4.18Kg




Size




Standard color



Test report



PDM



UGR < 19

Remark:

- Output data is from test result of 4ft PDM linear light fixture;
- Tolerance $\pm 10\%$;

Optional accessories

Installation accessories





- Recessed installation

L7380-BI

L7380-BI: Recessed bracket

Connection solution




Ac in line


- Connection

Ac in line: AC input cable

Disassembly tool



L-DA-D



L-DA-A

- Tool

L-DA-D: disassembly tool

L-DA-A: Rubber sucker