



Features

- Aluminum 6063, good heat radiation with long lifespan;
- The height of carrier could be adjustable;
- Magnet assembly, easy for installation and maintenance;
- Support 0~10V, PWM and Resistor dimming solution;
- High lighting efficiency, save energy;
- Long lifespan, ≥ 50000 hours;
- Light source adopts LM-80 certified LED;
- Adopt UL Class P certified power supply;



Parameter

Size	1230mm(4.03ft)X80mm(0.26ft)X35.5mm(0.12ft)
Beam angle	105°(PDM)
Working voltage	100~277VAC /50~60Hz
PF	≥ 0.9
Input power	31W (7.7W/ft)
CCT	3000K/4000K/6000K (3500K 、 5000K)
CRI	80+/90+
Lumen	2740~2840lm(685~710lm/ft)
Energy efficiency	A+
Dimming range	1~100%
Operating temperature	-20°C~+45°C
Storage temperature	-40°C~+60°C
Humidity	40~75% RH
IP grade	IP40
Installation way	Recessed
Package size	1280mm(4.20ft)X115mm(0.38ft)X92mm(0.3ft)
Gross Weight	2.1Kg

Size




Standard color



PDM

Installation accessories



- Recessed fixed

L-SM

Remark:

- Output data is from test result of 4ft PDM linear light fixture;
- Tolerance $\pm 10\%$;

Test report

