



Features

- Aluminum 6063, good heat radiation with long lifespan;
- The height of carrier could be adjustable;
- Magnet assembly, easy for installation and maintenance;
- Support 0~10V, PWM and Resistor dimming solution;
- High lighting efficiency, save energy;
- Long lifespan, ≥ 50000 hours;
- Light source adopts LM-80 certified LED;
- Adopt UL Class P certified power supply;



Parameter

| | |
|-----------------------|--|
| Size | 1839mm(6.03ft)X80mm(0.26ft)X35.5mm(0.12ft) |
| Beam angle | 105°(PDM) |
| Working voltage | 100~277VAC /50~60Hz |
| PF | ≥ 0.9 |
| Input power | 46W (7.7W/ft) |
| CCT | 3000K/4000K/6000K (3500K 、 5000K) |
| CRI | 80+/90+ |
| Lumen | 4115~4365lm(685~710lm/ft) |
| Energy efficiency | A+ |
| Dimming range | 1~100% |
| Operating temperature | -20°C~+45°C |
| Storage temperature | -40°C~+60°C |
| Humidity | 40~75% RH |
| IP grade | IP40 |
| Installation way | Recessed |
| Package size | 1890mm(6.20ft)X115mm(0.38ft)X92mm(0.3ft) |
| Gross Weight | 3.08Kg |

Size




Standard color



PDM

Installation accessories



- Recessed fixed

L-SM

Remark:

- Output data is from test result of 4ft PDM linear light fixture;
- Tolerance $\pm 10\%$;

Test report

