




Features

- Highlight SMD2835 + flexible FPC
- CRI80+/90+
- High brightness 1370~1518lm/m (418~463lm/ft)
- Light efficiency up to 156lm/W
- Precise cutting 71.4mm/unit (0.234ft/unit)
- Waterproof: IP20~IP67
- Working time ≥50000H
- Suitable for various dimming controllers

Standard CCT




Narrow spectrum



Impressive color consistency within 3 Step
MacAdam in the center BIN on the Planck
Locus over each individual LED, One Bin Only

Various waterproof solution




BV standard product

help to set up an energy conservation, flexible and multifunctional home lighting, the product with the features of low power, high brightness, high light efficiency, high CRI and high waterproof, various of connection accessories and dimming control systems are for choice


Parameter

Input voltage	24Vdc
Beam angle	120°
CCT	2700K/3000K/4000K/6000K (2300K/3500K/5000K)
CRI	80+/90+
Power	10W/m (3.05W/ft)
Current	0.42A/m (0.128A/ft)
Brightness	1370~1518lm/m (418~463lm/ft)
Length / reel	5M (16.4ft)
Cut length	71.4mm/unit (0.234ft/unit)
IP grade	IP20/IP55/IP65/IP66/IP67
Operating Temperature	-20℃~+45℃
Storage temperature	0℃~+60℃
Environment humidity	40~70% RH

Test report



Dimension





2700K
10W/m (3.05W/ft)
1370lm/m (418lm/ft)

3000K
10W/m (3.05W/ft)
1469lm/m (448lm/ft)

4000K
10W/m (3.05W/ft)
1557lm/m (475lm/ft)

6000K
10W/m (3.05W/ft)
1518lm/m (463lm/ft)

2300K
10W/m (3.05W/ft)
1337lm/m (408lm/ft)


3500K
10W/m (3.05W/ft)
1484lm/m (452lm/ft)

5000K
10W/m (3.05W/ft)
1533lm/m (467lm/ft)

Optional accessories



BV-SL8BB-2
IP20-8mm single color
for 30 ~ 120LED/m



BV-SL8XB-2
IP20-8mm single color
for 30 ~ 120LED/m



8mm-IP20
Splice Connector
(L) Snap connector
(T) Snap connector
(X) Snap connector



BV-SE-N8XB-2
IP20/IP55-8mm single color
for 30 ~ 120LED/m



BV-SE-N8BB-2
IP20/IP55-8mm single color
for 30 ~ 120LED/m



BV-XC-JXD-H2
DC/AC 300V10A
for 18 ~ 22AWG



BV-XC-JXD-T2
DC/AC 300V10A
for 18 ~ 22AWG



BV-XC-JXD-D2
DC/AC 300V6A
for 18 ~ 22AWG
Connectible




BV-XC-PD-1T02
DC/AC 300V6A
Compatible with BV-XC-JXD-D2, 1 for 2 connector

Triac dimming




Wireless dimmer




LED flexible strip

0-10V dimming



Dimmer




LED flexible strip

Smart dimming



wireless control



LED flexible strip